



Autohaus 3
Mercedes-Benz



Showroom & Customer Service

Electric Grey



MBEG / .12424UPS
24 x 24

Galactic Black



MBGB / .12424UPS
24 x 24

Blissful Oak




AV353.10636UPS
6 x 36

Shop & Service Areas

Crossville AutoPaver



AP880 > Onyx
3¾ x 8



AP001 > Grey Mingle
3¾ x 8

Account Manager

Frank Galifianakis
fgalifianakis@crossvilleinc.com

For pricing and order fulfillment, please contact:

Toni Hale
thale@crossvilleinc.com



Autohaus 3 Mercedes-Benz



Showroom and Customer Service

Technical Specifications

Electric Grey



Sizes & Finishes

Nominal (in)	Actual (mm)	Thickness (mm)	Finish	Application
24 x 24	597 x 597	9.5	UPS	Showroom Tile

Crossville® recommends a minimum grout joint of 3mm.
Actual measurements stated in inches indicate tile is calibrated (non-rectified). Actual measurements stated in mm indicate tile is rectified.

Product Performance

Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic COF

UPS	> 0.42	DCOF AcuTest™
-----	--------	---------------

Shade & Texture Index

Electric Grey has a shade variation of V3.



This porcelain tile product is produced with a V3 variation. You can expect clearly distinguishable differences in texture and/or pattern within similar colors.

Information listed here is subject to change.

Blissful Oak



Sizes & Finishes

Nominal (in)	Actual (mm)	Thickness (mm)	Finish
6 x 36	147 x 897	10.5	UPS

Note: All field tile is rectified and modular with a minimum 3mm grout joint.
Actual measurements stated in inches indicate tile is calibrated (non-rectified).
Actual measurements stated in mm indicate tile is rectified.

Product Performance

Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.42 - 0.52	AcuTest sm
-----	-------------	-----------------------

Shade & Texture Index

Blissful Oak has a shade variation of V3.



This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Galactic Black



Sizes & Finishes

Nominal (in)	Actual (mm)	Thickness (mm)	Finish	Application
24 x 24	597 x 597	9.5	UPS	Showroom Tile

Crossville® recommends a minimum grout joint of 3mm.
Actual measurements stated in inches indicate tile is calibrated (non-rectified). Actual measurements stated in mm indicate tile is rectified.

Product Performance


Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic COF

UPS	> 0.42	DCOF AcuTest™
-----	--------	---------------

Shade & Texture Index

Galactic Black has a shade variation of V3.



This porcelain tile product is produced with a V3 variation. You can expect clearly distinguishable differences in texture and/or pattern within similar colors.

Information listed here is subject to change.

Account Managers

Frank Galifianakis
fgalifianakis@crossvilleinc.com

For pricing and order fulfillment, please contact:

Toni Hale
thale@crossvilleinc.com



Shop & Service Areas

Technical Specifications

Crossville AutoPaver

Sizes (Available in all colors)

3-3/4 x 8

Sizes & Finishes

Field Tile - Rectified

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Finish
3-3/4 x 8	97 x 200	15	UPS

Crossville recommends a grout joint of 3mm.

Actual measurements stated in inches indicate tile is calibrated (non-rectified).

Actual measurements stated in mm indicate tile is rectified.

Product Performance

Breaking Strength	1,000 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

Unpolished	≥0.42	AcuTest sm
------------	-------	-----------------------

German Ramp Value

Unpolished	R10	DIN 51130
------------	-----	-----------

Shade & Texture Index

AutoPaver has a shade variation of V1.

V1	V2	V3	V4	V1 Uniform appearance
				
				V2 Slight Variation
				V3 Moderate Variation
				V4 Substantial Variation

This porcelain tile product is produced with a V1 variation. Differences among pieces from the same production run are minimal.

Account Managers

Frank Galifianakis
fgalifianakis@crossvilleinc.com

For pricing and order fulfillment, please contact:

Toni Hale
thale@crossvilleinc.com